

TANKS CINERATANK

<u>=QUICK</u> © GREEŇ © LOW COST



Why choose our PE tanks? PE tanks from 4m³ to 192m³ delivered

1-22m long

600-3200mm 🖉

diameter

on-site

Current lead time: 4 weeks

Easily connected

Fully recyclable

OVER

100-year design life



SIZE

Totally flexible design: sumps risers, connectors

Pricing

Depending upon freight, burial levels, connections, access points and washdown etc.

FAQs

Can INFRAPIPE™ tanks incorporate washdown systems?

Absolutely, HDPE easily accommodates internal systems.

Are they trafficable?

Yes! INFRAPIPE™ tanks can be designed to take any load with as little as minimum 600mm of cover.

What are the requirements for installation? Typical bedding material is GAP 20/40.

How easy is access to the inside of an INFRAPIPETM tank?

INFRAPIPE™ tanks can be designed with as many manholes and ladders as required.

Is flotation an issue for INFRAPIPE™ tanks? For sites with a high ground water table, fittings can be supplied to avoid the risk of flotation.

Do we need a professional design service? No. INFRAPIPE[™] need the soil details and will then design it for you.

What types of connections are available with these tanks?

Our tanks provide connection options such as flanged, threaded or butt-welded based on factors like tank material thickness, flow rate, and stored liquid type.

Can we modify this tank?

Yes, the beauty of HDPE is at a later date you can modify, create or remove connections.













ISO TYPE 5 AS/NZS 5065:2005 AMI:74961

ISO TYPE 5 AS/NZS 4130:2018 AMI:74999





(a) 09 869 3030

FOLLOW US: 📊 🖸 INFRAPIPE NZ